

Austria

Forbo - Contel Handelsgesellschaft mbH
Handelskai 52 (Eingang Wehlstr. 29)
A-1200 Wien
Austria
Tel: +43 1 330 92 01
Fax: +43 1 330 92 10
E-mail: info.austria@forbo.com
Internet: www.forbo-flooring.at

Czech & Slovak Republic

Forbo s.r.o.
Novodvorská 994
142 21 Praha 4
Česká republika
Tel: + 420 239 043 011
Fax: + 420 239 043 012
E-mail: info@forbo.cz
www.forbo-flooring.cz

Ireland

Forbo Ireland Ltd.
2 Deansgrange Business Park
Blackrock, Co Dublin
Tel: 00353 1 2898 898
Fax: 00353 1 2898 177
E-mail: info.ireland@forbo.com
www.forbo-flooring.ie

Poland

Forbo Flooring Poland
ul. Wolsztyńska 2
60-361 Poznań
Tel: +48 61 862 13 82
Fax: +48 61 622 99 71
E-mail: info@forbo-flooring.pl
www.forbo-flooring.pl

Switzerland

Forbo - Giubiasco SA
Via Industrie 16
CH - 6512 Giubiasco
Switzerland
Tel: +41 91 850 01 11
Fax: +41 91 850 01 41
E-mail: info.flooring.ch@forbo.com
Internet: www.forbo-flooring.ch

Baltic States

Forbo Flooring
K. Ulmana gatve 5
Riga, LV-1004, Latvia
Tel: +371 670 66 116
Fax: +371 670 66 117
E-mail: info.lv@forbo.com
www.forbo-flooring.com

Danmark

Forbo Flooring A/S
Produktionsvej 14
2600 Glostrup
Tlf: 44 92 85 00
Fax: 44 92 85 20
E-Mail: info.denmark@forbo.com
www.forbo-flooring.dk

Middle-East/Turkey/Maghreb/Africa

French Overseas Territories/Greece
Forbo Flooring Systems
63, rue Gosset – BP 2717
51100 REIMS Cedex
France
Tél. 00 333 26 77 35 00
Fax 00 333 26 07 18 93
Info-produits@forbo.com
www.forbo-flooring.com

Russia

Forbo Flooring
105082 Moscow
2nd Irininsky per. 3/5, str 1
office 400
Tel: +7-495-7855774
+7-495-7855799
Fax: +7-495-7852729
E-mail: forbo-rus@elnet.msk.ru
www.forbo.ru
www.linoleum.ru

United Kingdom

Forbo-Nairn Ltd.
P.O. Box 1, Kirkcaldy
Fife, KY1 2SB
Tel: 01592 643777
Samples: 0800 731 2369
Fax: 01592 643999
E-mail: info.uk@forbo.com
www.forbo-flooring.co.uk

Belgium

Forbo Flooring
Noordkustlaan 18
1702 Groot-Bijgaarden
Tel: +32 2 464 10 10
Fax: +32 2 464 10 11
info.belgium@forbo.com
www.forbo-flooring.be

Finland

Forbo Flooring AB Finland
Heikkiläntie 2, 4 krs
00210 Helsinki
Puhelin +358 (0)9 862 30 300
Faksi +358 (0)9 862 30 301
Sähköposti: info.finland@forbo.com
www.forbo-flooring.fi

Netherlands

Forbo Flooring B.V.
Postbus 13
1560 AA Krommenie
Tel: (075) 647 78 80
Fax: (075) 628 37 71
contact@forbo.com
www.forbo-flooring.nl

Spain

Forbo Pavimentos S.A.
Pasaje Bofill, 13-15
08013 Barcelona
Tel: +34 93 20 90 793 – 93 20 06 732
Fax: +34 93 245 69 60
E-mail: info@forbo-linoleum.es
Internet: www.forbo-flooring.es

Other countries

Forbo Flooring B.V.
P.O. Box 13
1560 AA Krommenie
The Netherlands
Tel: +31 75 647 74 77
Fax: +31 75 647 77 01
E-mail: contact@forbo.com
www.forbo-flooring.com

Brasil

Forbo Pisos Ltda.
Rua Laguna, 708 - Santo Amaro
04728-001 - São Paulo - SP - Brasil
Tel.: +55 11 5641-8228
Fax: +55 11 5643-9828
E-mail: info@forbo-linoleum.com.br
Internet: www.forbo-linoleum.com.br

Hungary

Forbo Flooring Hungary
Megyeri út 8.
H-1044 Budapest
Tel.: + 36 12 72 05 63
Fax: + 36 12 72 05 63
E-mail: info.hungary@forbo.com
www.forbo-flooring.hu

Norway

Forbo Flooring AS
Hagaløkkveien 7
1383 Asker
Tlf: 66 77 12 00
Fax: 66 77 12 40
E-Mail: info.norway@forbo.com
www.forbo-flooring.no

Sweden

Forbo Flooring AB
Box 172, 401 22 Göteborg
Tel.: 031-89 20 00.
Fax: 031-28 44 47
Stockholm: Tel: 08-602 34 90
E-Mail: info.sweden@forbo.com
www.forbo-flooring.se



westbond®
carpet tiles

Plain - N9000XL & wool
Flex - nylon & wool
natural

Forbo

FLOORING SYSTEMS

creating better environments

creating better environments

Forbo

FLOORING SYSTEMS



Let the world inspire your creativity. Realise it with Westbond.

Westbond carpet tiles are synonymous with total flexibility and sophistication. Blending yarns to order and manufacturing premium quality fusion bonded tiles in an almost infinite number of colourways, with no minimum order quantity.

Westbond allows customers to take control of the process of designing luxurious, bespoke carpet tiles with exceptionally heavy pile weights for the most prestigious installations.

Fusion bonding is a sophisticated method of carpet tile manufacture where individual yarn pile is bonded onto the backing material to make an extremely dense and luxurious product.

Each tuft is individual and a high proportion of the yarn is in the wear surface providing a beautiful, rich velour carpet tile which gives an excellent broadloom appearance.



Exclusive & luxurious carpet tiles in your own colour from 1m²

Let the world inspire your creativity



You will discover our inspiring collection of no less than 160 fresh and exciting shades which is intended to stimulate your imagination.

westbond® ibond




All colours are available in a variety of qualities including polyamide or wool, and pile weights up to 2400g/m². Please see the technical specifications page for more information.

westbond® ibond



All colours are available in a variety of qualities including polyamide or wool, and pile weights up to 2400g/m². Please see the technical specifications page for more information.

westbond® ibond



All colours are available in a variety of qualities including polyamide or wool, and pile weights up to 2400g/m². Please see the technical specifications page for more information.

westbond® ibond



All colours are available in a variety of qualities including polyamide or wool, and pile weights up to 2400g/m². Please see the technical specifications page for more information.

Beautiful Tuscan morning blue?




We understand that colour is intensely personal. It has to be just right. So if you can't find that perfect shade, why not come up with your own? We offer any colour, richly dyed to your unique vision, with no minimum sales order.

The colour possibilities are only limited by your imagination, and unrivalled luxury is ensured through a wide range of qualities and yarns.

westbond[®] flex



Choose your own colours...
...then combine them into a truly unique floor



westbond[®] flex



Create your own carpet tile with a flex combination from just 1m².

The Flex carpet tile is unique to Westbond and offers the ideal solution for those seeking an individual look to the floor. Simply create your own carpet tile design by selecting colours from the ibond range in a flex combination.

The results of your creativity can be easily and quickly realised with a sample to show you what the finished product will look like, despatched within 24 hours.




ibond plains



NF92145 | valentine's day NF92144 | pink splash NF92146 | oaked claret




NF92165 | tutti frutti NF92147 | midnight ruby NF92148 | cocoa liqueur



NF92149 | dark woodland NF92150 | deep ruby NF92151 | africa slate




NF92118 | chocolate orange NF92152 | walnut whip NF92153 | curry spice



NF92141 | orange peel NF92082 | cinnamon NF92078 | goldcup

ibond plains





We have used our knowledge and expertise to create a core collection of 30 flex combinations which are shown below to stimulate your imagination...



The Flex patterning concept is available in both polyamide and wool in a wide variety of pile weights.*

ibond plains



WF152134 | cut grass WF152154 | granite stone WF152155 | gale force




WF152156 | spruce forest WF152157 | arctic circle WF152158 | fossil stone



WF152061 | gushing stream WF152159 | gulf stream WF152160 | jet graphite




WF152161 | capri foam WF152162 | deepwater tint WF152121 | blue john stone



WF152163 | ocean rain WF152164 | indian ink WF152093 | star cloud

ibond plains



* Please refer to the technical specifications page for further details.

Undyed wool

Westbond Natural is a unique collection of commercial carpet tiles containing pure and natural undyed wool. The range is the perfect answer to today's ecological concerns.

The carpet tile backing minimises environmental impact through its use of up to 74% recycled materials and wool is a sustainable, natural and renewable resource.

Natural colours

The colours are derived from a blend of fleeces from seven different sheep breeds, Herdwick, Swaledale, Shetland, The Derbyshire Gritstone, The Jacob, Dales Bred

and Cheviot, resulting in a warm palette of taupes, creams, beiges and umber.






westbond® natural




W12921U | tussock



W12791U | hampshire



W12797U | honiton



W12790U | masham




W12789U | manx

The Westbond Natural collection is available in weights of 1200gsm and 2400gsm.



W12795U | dorset



W12794U | rutland




Technical specifications

Item	N9000XL & Flex Nylon	Wool & Wool Flex	Wool Natural	
Description	Fusion bonded cut pile carpet tile	Fusion bonded cut pile carpet tile	Fusion bonded cut pile carpet tile	
 Dimensions	50cm x 50cm 18 tiles per box	50cm x 50cm 14 tiles / 14 tiles / 10 tiles per box	50cm x 50cm 18 tiles / 10 tiles per box	
Total thickness	8.1mm ± 10%	10.0mm / 11.0mm / 14.0mm ± 10%	8.1 / 14.0mm ± 10%	
Installation Method	Broadloom	Broadloom	Broadloom	
Pile composition	100% polyamide	80% British wool / 10% polyamide / 10% polyester	80% Undyed British wool / 10% polyamide / 10% polyester	
Dye Method	Hank dyed	Hank dyed	Blended Wool (undyed)	
Pile Weight ± 10%	950gsm	1500 / 1800 / 2400gsm	1200 / 2400gsm	
 Total weight	4,000gsm ± 10%	4,500 / 4,800 / 5,400gsm ± 10%	4,300 / 5,400gsm ± 10%	
Pile density Grams per cm ³	0.149 /cm ³	0.167 / 0.187 / 0.167 /cm ³	0.170 / 0.170 /cm ³	
Tuft density Tufts per m ²	272,000 /m ²	360,000 / 407,000 / 360,000 /m ²	366,000 / 366,000 /m ²	
Tile backing	PVC incorporating up to 74% pre-consumer recycled content			
 Application	EN 1307	Class 33	Class 32	
		Suitable for any type of heavy contract application	Suitable for general commercial applications	Suitable for general commercial applications
 Dimensional stability	EN 986	≤0.2 %	≤0.2 %	≤0.2 %
 Castor chair	EN 985	Minimum R Value: ≥ 2.4	Minimum R Value: ≥ 2.4	Minimum R Value: ≥ 2.4
 Light fastness	EN ISO 105-B02	>5	>5	>5
 Electrical resistance	EN 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage < 2kV.		
Environmental	Materials used in the construction of Westbond carpet tiles are chosen for their low volatile organic compound (VOC) levels.			
Guarantee	Westbond N9000XL & Flex Nylon are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force. Westbond wool products are guaranteed for 7 years.			
 CE	Westbond fusion bonded products meet the requirements of EN 14041			
 Reaction to fire	EN 13501-1	B _f s1	C _f s1	C _f s1
 Slip resistance	EN 13893	NPD	NPD	NPD

Forbo reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

Weights



950g/m² polyamide

1500g/m² wool

1800g/m² wool

2400g/m² wool

Installation and Maintenance:

Shades may vary from batch to batch and should be checked before installation. Batches should not be mixed in the same location. All Westbond products are to be installed in full accordance with Forbo installation instructions and recognised trade standards.



Recycled backing:

All Westbond carpet tiles utilise a recycled mixed vinyl waste backing which contains up to 74% pre-consumer recycled content in order to minimise environmental impact. The process uses existing Forbo technology which accesses PVC waste streams from a number of our factories, and also those of competitors within the flooring industry, thereby decreasing the amount of waste material which would otherwise be sent to landfill.

Forbo FloorCare method

Westbond tiles

Care and maintenance of Westbond products is essential for their longevity and appearance. Soiling and general wear adversely affect the appearance of carpet tiles and should be countered by an effective cleaning programme. A regular cleaning programme will minimise the need for major restorative maintenance. Also make sure you install an entrance barrier matting at every exterior entrance. Avoid excessive use of cleaning products. If used, rinse them out thoroughly, as any residue may attract dirt.

Cleaning after installation



- Vacuum clean the floor using an upright vacuum cleaner with a powered brush
- Remove stains or spills locally using clean warm water
- Always work from outside inwards
- Remove excess water
- Allow the floor to dry

Regular cleaning



- Vacuuming
- Regular vacuuming, using an upright vacuum cleaner with a powered brush, is the essential first step in the upkeep of the installation. Heavy traffic areas require more frequent vacuuming than those areas which are less frequented.



- Spot and stain removal
- A daily spot and stain removal process should also be implemented using a neutral spotting detergent. The stain should not be allowed to dry as this can make removal more difficult.

Periodic maintenance



Vacuuming will not easily remove oily residues from carpet tiles nor the balance of dry soiling. Systems have been developed to maintain appearance longer and remove some of the soiling. These systems allow carpet tiles to be maintained on a periodic basis.

- Rotary shampoo: using rotating brushes and a crystallising shampoo
- Hot water extraction: a very effective way to remove heavy soiling.

Extensive Clean & Care instructions are available at your local Forbo Flooring sales office. Please read this before starting any corrective care or stain removal.